

## Technische Daten

## Produktgruppe 81:

Artikel- Nummer	Innen- Ø	Außen- Ø	Wand- stärke	Gewicht kg/100 m	Biege- radius	Betriebs- druck Wasser	Berst- druck	Rollenlänge m
.	mm	mm	mm	kg/100 m	mm	bar	bar	m
<b>81 004 30</b>	4,0	10,0	3,0	8,4	15,0	28	84	50
<b>81 005 30</b>	5,0	11,0	3,0	9,6	18,0	28	84	50
<b>81 006 30</b>	6,0	12,0	3,0	10,8	25,0	25	75	50
<b>81 008 30</b>	8,0	14,0	3,0	13,2	30,0	24	72	50
<b>81 009 30</b>	9,0	15,0	3,0	14,4	35,0	22	66	50
<b>81 010 30</b>	10,0	16,0	3,0	15,6	40,0	21	63	50
<b>81 012 30</b>	12,0	18,0	3,0	18,0	55,0	17	51	50
<b>81 012 45</b>	12,0	21,0	4,5	29,7	55,0	17	51	50
<b>81 125 30</b>	12,5	18,5	3,0	18,6	55,0	15	45	50
<b>81 013 30</b>	13,0	19,0	3,0	19,2	70,0	15	45	50
<b>81 013 35</b>	13,0	20,0	3,5	23,1	72,0	16	48	50
<b>81 015 30</b>	15,0	21,0	3,0	21,6	75,0	15	45	50
<b>81 016 35</b>	16,0	23,0	3,5	27,3	75,0	15	45	50
<b>81 016 40</b>	16,0	24,0	4,0	32,0	75,0	15	45	50
<b>81 019 35</b>	19,0	26,0	3,5	31,5	130,0	10	30	50
<b>81 019 40</b>	19,0	27,0	4,0	36,8	130,0	11	33	25/50
<b>81 025 40</b>	25,0	33,0	4,0	46,4	200,0	9	27	25/50
<b>81 025 45</b>	25,0	34,0	4,5	53,1	220,0	8	24	25/50
<b>81 030 40</b>	30,0	38,0	4,0	54,4	250,0	7	21	25/50
<b>81 032 50</b>	32,0	42,0	5,0	74,0	310,0	8	24	25/50
<b>81 038 50</b>	38,0	48,0	5,0	86,0	420,0	6	18	25/50
<b>81 045 50</b>	45,0	55,0	5,0	100,0	550,0	4	12	25
<b>81 050 50</b>	50,0	60,0	5,0	110,0	650,0	4	12	25